# SAFETY DATA SHEET



Revision Date 23-Jun-2015

Version 2

# 1. Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name DIESEL GUARD ANTI-GEL DEICER ADDITIVE

Product code F537

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Fuel additive

Restrictions on use No information available

1.3 Details of the supplier of the safety data sheet

Supplier Legend Brands

15180 Josh Wilson Road Burlington, WA 98233 800-932-3030

1.4 Emergency telephone number

Emergency telephone number INFOTRAC 1-800-535-5053 (North America)

1-352-323-3500 (International)

# 2. Hazards identification

### 2.1 Classification of the substance or mixture

## GHS Classification in accordance with 29 CFR 1910.1200

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Carcinogenicity	Category 2
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Aspiration toxicity	Category 1
Flammable liquids	Category 3

## 2.2 Label elements

## Signal Word

Danger

#### **Hazard Statements**

Causes skin irritation
Causes serious eye irritation
Suspected of causing cancer
May cause respiratory irritation
May be fatal if swallowed and enters airways
Flammable liquid and vapor



## **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Wash face, hands and any exposed skin thoroughly after handling

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/Bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

### **Precautionary Statements - Response**

Call a POISON CENTER or doctor/physician if you feel unwell If exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### 2.3. Other Hazards Hazards not otherwise classified (HNOC)

Not Applicable

#### 2.4 Other information

Not Applicable

# 3. Composition/Information on Ingredients

<u>Substance</u> Not applicable **Mixture** 

Chemical Name	CAS-No	Weight %
AROMATIC PETROLEUM DISTILLATES	64742-95-6	50 - 60
1,2,4-Trimethylbenzene	95-63-6	20 - 30
HEAVY AROMATIC NAPHTHA	64742-94-5	10 - 20
Glycol ether (non-HAP)	Proprietary	5 - 10

Xylene	1330-20-7	1 - 5
CUMENE	98-82-8	< 1
NAPHTHALENE	91-20-3	< 1

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. First aid measures

## 4.1 Description of first-aid measures

General advice For further assistance, contact your local Poison Control Center.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Call a physician or poison control center

immediately.

**Skin contact**Wash off immediately with soap and plenty of water for at least 15 minutes while removing

all contaminated clothing and shoes. Call a physician if irritation develops or persists. Wash

contaminated clothing before reuse.

**Inhalation** Move victim to fresh air. If not breathing, give artificial respiration. Seek immediate medical

attention/advice.

**Ingestion** Gently wipe or rinse the inside of the mouth with water. Never give fluids if the victim is

unconscious or having convulsions. Do NOT induce vomiting. If a person vomits when lying on his back, place him in the recovery position. Call a physician or poison control center

immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms See Section 2.2, Label Elements and/or Section 11, Toxicological effects.

#### 4.3 Recommendations for immediate medical care and/or special treatment

Notes to physician There is no specific antidote for effects from overexposure to this material. Treat

symptomatically.

### 5. Fire-Fighting Measures

## 5.1 Extinguishing media

#### Suitable extinguishing media

Foam Carbon dioxide (CO<sub>2</sub>) Dry chemical Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

Unsuitable Extinguishing Media Water may be unsuitable for extinguishing fires.

#### 5.2 Specific hazards arising from the substance or mixture

#### **Special Hazard**

Thermal decomposition can lead to release of irritating gases and vapors Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks)

Hazardous Combustion Products Possible formation of carbon oxides, nitrogen oxides, and hazardous organic compounds.

## **Explosion Data**

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge No information available.

## 5.3 Advice for firefighters

Evacuate personnel to safe areas. Move non-burning material, as feasible, to a safe location as soon as possible. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers with flooding quantities of water until well after fire is out. Thoroughly decontaminate all protective equipment after use.

DO NOT extinguish a fire resulting from the flow of flammable liquid until the flow of the liquid is effectively shut off. This precaution will help prevent the accumulation of an explosive vapor-air mixture after the initial fire is extinguished.

## 6. Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do it without risk. Refer to protective measures listed in sections 7 and 8. Avoid exceeding of the given occupational exposure limits (see section 8). Personal protection needs must be evaluated based on information provided on this sheet and the special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred, and the training and the expertise of employees in the area responding to the spill.

#### 6.2 Environmental precautions

Prevent product from entering drains. Prevent entry into waterways, sewers, basements or confined areas.

# 6.3 Methods and materials for containment and cleaning up

Methods for Containment Absorb with earth, sand or other non-combustible material and transfer to containers for

later disposal. Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Use a non-combustible material like vermiculite, sand or earth to soak up the product and

place into a container for later disposal. Ground and bond containers when transferring

material. Take precautionary measures against static discharges.

## 7. Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety

practice. Avoid contact with skin, eyes and clothing. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product. Use according to package label instructions. Empty containers may retain product residue or vapor. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Take measures to prevent the build up of electrostatic charge.

Hygiene measures Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this

product. Remove and wash contaminated clothing before re-use. Wash hands before

breaks and immediately after handling the product.

# 7.2 Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and

sources of ignition. Keep in properly labeled containers. Keep away from food, drink and

animal feedingstuffs.

Materials to Avoid No materials to be especially mentioned.

## 8. Exposure controls/personal protection

## 8.1 Occupational Exposure Limits (OEL)

Chemical Name	ACGIH TLV	OSHA PEL	British Columbia	Alberta	Quebec	Ontario TWAEV
Glycol ether	STEL: 150 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm
(non-HAP)	TWA: 100 ppm	TWA: 600 mg/m <sup>3</sup>	STEL: 150 ppm	TWA: 606 mg/m <sup>3</sup>	TWA: 606 mg/m <sup>3</sup>	STEL: 150 ppm
	S*	S*	Skin	STEL: 150 ppm	STEL: 150 ppm	Skin
				STEL: 909 mg/m <sup>3</sup>	STEL: 909 mg/m <sup>3</sup>	
				Skin	Skin	
Xylene	STEL: 150 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m <sup>3</sup>	STEL: 150 ppm	TWA: 434 mg/m <sup>3</sup>	TWA: 434 mg/m <sup>3</sup>	STEL: 150 ppm
				STEL: 150 ppm	STEL: 150 ppm	

				STEL: 651 mg/m <sup>3</sup>	STEL: 651 mg/m <sup>3</sup>	
CUMENE 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m <sup>3</sup> S*	TWA: 25 ppm STEL: 75 ppm	TWA: 50 ppm TWA: 246 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 246 mg/m <sup>3</sup>	TWA: 50 ppm
NAPHTHALENE 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m <sup>3</sup>	TWA: 10 ppm STEL: 15 ppm Skin	TWA: 10 ppm TWA: 52 mg/m³ STEL: 15 ppm STEL: 79 mg/m³ Skin	TWA: 10 ppm TWA: 52 mg/m³ STEL: 15 ppm STEL: 79 mg/m³	TWA: 10 ppm STEL: 15 ppm Skin

#### 8.2 Appropriate engineering controls

**Engineering Measures** Ensure adequate ventilation, especially in confined areas. Use adequate ventilation to

maintain airborne concentrations at levels below permissible or recommended occupational

exposure limits.

### 8.3 Individual protection measures, such as personal protective equipment

Eye/Face Protection Wear chemical-resistant glasses and/or goggles and a face shield when eye and face

contact is possible due to handling and processing of material.

**Skin and body protection** Wear impervious gloves and/or clothing if needed to prevent contact with the material.

Rubber/latex/neoprene or other suitable chemical resistant gloves. Remove and wash

contaminated clothing before re-use. Cotton-blend coveralls.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Respiratory protection must be provided in

accordance with current local regulations.

Hygiene measures See section 7 for more information

# 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state Liquid
Appearance Clear
Color various

Odor Hydrocarbon-like
Odor Threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Methods</u>

**pH** not applicable

Melting/freezing point

No information available

Boiling point/boiling range No information available

Flash Point 52 °C / 126 °F

Evaporation rateNo information availableFlammability (solid, gas)No information available

Flammability (solid, gas)

Flammability Limits in Air

upper flammability limitNo information availablelower flammability limitNo information availableVapor pressureNo information available

Vapor density

No information available

Specific Gravity 0.869

Water solubilityNo information availableSolubility in other solventsNo information availablePartition coefficientNo information availableAutoignition temperatureNo information availableDecomposition temperatureNo information available

Viscosity, kinematic < 20 mm2/s

Viscosity, dynamic No information available

**Explosive properties**No information available **Oxidizing Properties**No information available

9.2 Other information

Volatile organic compounds (VOC) No information available

content

**Density** 7.25 lb/gal

## 10. Stability and Reactivity

## 10.1 Reactivity

No data available

### 10.2 Chemical stability

Stable under recommended storage conditions.

### 10.3 Possibility of hazardous reactions

None under normal processing.

#### 10.4 Conditions to Avoid

Keep away from heat, sparks and flames.

## 10.5 Incompatible Materials

None known based on information supplied.

## 10.6 Hazardous Decomposition Products

None under normal use conditions. Thermal decomposition can lead to release of irritating gases and vapors.

\_\_\_\_\_

# 11. Toxicological information

### 11.1 Acute toxicity

Numerical measures of toxicity: Product Information

The following values are calculated based on chapter 3.1 of the GHS document

 Oral LD50
 5,554.00 mg/kg

 Dermal LD50
 10,867.00 mg/kg

 Vapor
 62.00 mg/l

Numerical measures of toxicity: Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
AROMATIC PETROLEUM DISTILLATES 64742-95-6	-	> 2000 mg/kg(Rabbit)	= 3400 ppm(Rat)4 h
1,2,4-Trimethylbenzene 95-63-6	3280 mg/kg ( Rat )	> 3160 mg/kg (Rabbit)	= 18 g/m³(Rat)4 h
HEAVY AROMATIC NAPHTHA 64742-94-5	5000 mg/kg ( Rat )	> 2 mL/kg(Rabbit)	> 590 mg/m³(Rat)4 h
Glycol ether (non-HAP)	5230 mg/kg ( Rat )	= 9500 mg/kg(Rabbit)	-
Xylene 1330-20-7	3500 mg/kg ( Rat )	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
CUMENE 98-82-8	1400 mg/kg (Rat)	= 12300 μL/kg(Rabbit)	8700 ppm (Rat) 4-h
NAPHTHALENE 91-20-3	1110 mg/kg ( Rat )	= 1120 mg/kg(Rabbit)	> 340 mg/m³(Rat)1 h

# 11.2 Information on toxicological effects

#### Skin corrosion/irritation

Product Information

- No information available
- Component Information
- No information available

## Eye damage/irritation

Product Information

- No information available
- Component Information
- No information available

### Respiratory or skin sensitization

Product Information

- No information available
- Component Information
- No information available

## **Germ Cell Mutagenicity**

Product Information

- No information available
- Component Information
- No information available

### Carcinogenicity

Product Information

• The table below indicates whether each agency has listed any ingredient as a carcinogen Component Information

Chemical Name	ACGIH	IARC	NTP	OSHA
CUMENE	-	Group 2B	Reasonably Anticipated	
98-82-8				
NAPHTHALENE	-	Group 2B	Reasonably Anticipated	
91-20-3		•		

# Reproductive toxicity

Product Information

• No information available

Component Information

· No information available

## STOT - single exposure

No information available

## STOT - repeated exposure

No information available

#### Other adverse effects

**Target Organs** 

- Blood
- · Central nervous system
- Eyes
- Respiratory system
- Skin

Product Information

- No information available
- Component Information

• No information available

## **Aspiration hazard**

Product Information

• Risk of serious damage to the lungs (by aspiration)

Component Information

· No information available

# 12. Ecological information

### 12.1 Toxicity

**Ecotoxicity** 

No information available

< 1 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

**Ecotoxicity effects** 

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
AROMATIC PETROLEUM DISTILLATES 64742-95-6	-	LC50: 96 h Oncorhynchus mykiss 9.22 mg/L	EC50: 48 h Daphnia magna 6.14 mg/L
1,2,4-Trimethylbenzene 95-63-6	-	LC50: 96 h Pimephales promelas 7.19 - 8.28 mg/L flow-through	EC50: 48 h Daphnia magna 6.14 mg/L
HEAVY AROMATIC NAPHTHA 64742-94-5	-	LC50: 96 h Pimephales promelas 19 mg/L static LC50: 96 h Oncorhynchus mykiss 2.34 mg/L LC50: 96 h Lepomis macrochirus 1740 mg/L static LC50: 96 h Pimephales promelas 45 mg/L flow-through LC50: 96 h Pimephales promelas 41 mg/L	EC50: 48 h Daphnia magna 0.95 mg/L
Glycol ether (non-HAP)	<del>-</del>	LC50: 96 h Pimephales promelas	LC50: 48 h Daphnia magna 1919

23-Jun-2015 - DGAWBK - 2 - AGHS - English -

		10000 mg/L static	mg/L
Xylene	-	LC50: 96 h Pimephales promelas	EC50: 48 h water flea 3.82 mg/L
1330-20-7		23.53 - 29.97 mg/L static LC50: 96	LC50: 48 h Gammarus lacustris 0.6
		h Cyprinus carpio 780 mg/L	mg/L
		semi-static LC50: 96 h Cyprinus	
		carpio 780 mg/L LC50: 96 h Poecilia	
		reticulata 30.26 - 40.75 mg/L static	
		LC50: 96 h Pimephales promelas	
		13.4 mg/L flow-through LC50: 96 h	
		Oncorhynchus mykiss 2.661 - 4.093	
		mg/L static LC50: 96 h	
		Oncorhynchus mykiss 13.5 - 17.3	
		mg/L LC50: 96 h Lepomis	
		macrochirus 13.1 - 16.5 mg/L	
		flow-through LC50: 96 h Lepomis	
		macrochirus 19 mg/L LC50: 96 h	
		Lepomis macrochirus 7.711 - 9.591	
		mg/L static	
CUMENE	EC50: 72 h Pseudokirchneriella	LC50: 96 h Pimephales promelas	EC50: 48 h Daphnia magna 0.6
98-82-8	subcapitata 2.6 mg/L	6.04 - 6.61 mg/L flow-through LC50:	mg/L EC50: 48 h Daphnia magna
		96 h Oncorhynchus mykiss 4.8	7.9 - 14.1 mg/L Static
		mg/L flow-through LC50: 96 h	
		Oncorhynchus mykiss 2.7 mg/L	
		semi-static LC50: 96 h Poecilia	
		reticulata 5.1 mg/L semi-static	
NAPHTHALENE	<del>-</del>	LC50: 96 h Pimephales promelas	LC50: 48 h Daphnia magna 2.16
91-20-3		5.74 - 6.44 mg/L flow-through LC50:	mg/L EC50: 48 h Daphnia magna
		96 h Oncorhynchus mykiss 1.6	1.96 mg/L Flow through EC50: 48 h
		mg/L flow-through LC50: 96 h	Daphnia magna 1.09 - 3.4 mg/L
		Oncorhynchus mykiss 0.91 - 2.82	Static
		mg/L static LC50: 96 h Pimephales	
		promelas 1.99 mg/L static LC50: 96	
		h Lepomis macrochirus 31.0265	
		mg/L static	

# 12.2 Persistence and degradability

No information available.

# 12.3 Bioaccumulative potential

Discharge into the environment must be avoided

Chemical Name	log Pow
1,2,4-Trimethylbenzene 95-63-6	3.63
HEAVY AROMATIC NAPHTHA 64742-94-5	6.1
Glycol ether (non-HAP)	-0.064
Xylene 1330-20-7	3.15
CUMENE 98-82-8	3.55
NAPHTHALENE 91-20-3	3.3

# 12.4 Mobility in soil

No information available.

# 12.5 Other adverse effects

No information available

# 13. Disposal Considerations

## 13.1 Waste Disposal Guidance

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

# 14. Transport Information

Note This product is not regulated by US DOT when shipped by ground in containers < 119

gallons.

DOT

Proper shipping name NA1993, Combustible liquid, n.o.s. (petroleum distillates, 1,2,4-trimethylbenzene), 3, III

MEX no data available

<u>IMDG</u>

Proper shipping name UN1993, Flammable liquid, n.o.s. (petroleum distillates, 1,2,4-trimethylbenzene), 3, III

IATA

Proper shipping name UN1993, Flammable liquid, n.o.s. (petroleum distillates, 1,2,4-trimethylbenzene), 3, III

## 15. Regulatory information

Ultra Low Sulfur Additives: The sulfur content of this Diesel Fuel Additive does not exceed 15 parts per million (ppm). References: Code of Federal Regulations Title 40 Part 80, EPA 2006 Regulation of Fuels and Fuel Additives, EPA Document # EPA40-F-05-013.

### 15.1 International Inventories

TSCA Complies DSL Complies

EINECS/ELINCS -

ENCS -

IECSC Complies
KECL Complies
PICCS -

AICS Complies

NZIoC -

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL** - Canadian Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

#### 15.2 U.S. Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	SARA 313 - Threshold Values %
1,2,4-Trimethylbenzene 95-63-6	1.0
Glycol ether (non-HAP)	1.0

Xylene 1330-20-7	1.0
NAPHTHALENE 91-20-3	0.1

#### 15.3 Pesticide Information

Not applicable

## 15.4 U.S. State Regulations

## **California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
CUMENE - 98-82-8	Carcinogen
NAPHTHALENE - 91-20-3	Carcinogen

## 16. Other information

NFPA Health Hazard 2 Flammability 2 Instability 0 Physical and chemical hazards 
HMIS Health Hazard 2\* Flammability 2 Physical Hazard 0 Personal protection X

#### Legend:

ACGIH (American Conference of Governmental Industrial Hygienists)

Ceiling (C)

DOT (Department of Transportation)

EPA (Environmental Protection Agency)

IARC (International Agency for Research on Cancer)

International Air Transport Association (IATA)

International Maritime Dangerous Goods (IMDG)

NIOSH (National Institute for Occupational Safety and Health)

NTP (National Toxicology Program)

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

PEL (Permissible Exposure Limit)

Reportable Quantity (RQ)

Skin designation (S\*)

STEL (Short Term Exposure Limit)

TLV® (Threshold Limit Value)

TWA (time-weighted average)

Revision Date

23-Jun-2015

**Revision Note** 

No information available

#### **Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**